

# **TECHNICAL DATA SHEET - MARKKLOSS**

# DESCRIPTION

Markkloss is a reinforcement spacer for bottom reinforcement in reinforced concrete structures. The large "openings" in the spacer allow maximum concrete flow, ensuring that the reinforcement is fully embedded in concret.

The wide base and "tower-shape" of the spacer is designed to withstand high loads.

## USAGE

Use on soft surfaces such as insulation, sand, gravel, plastic foil or sheeting, etc.

## TECHNICAL INFORMATION

#### Color: Grey

Material: A blend of PVC-free PP and PE (Polyolefin blend)

**Concrete cover:** 15-100 mm (See stock assortment in the table below)

**Rebar:** Ø4-16 mm

Material consumption: 3-5 pcs/m<sup>2</sup>

Package: Packed in cardboard boxes.

#### **RANGE OF ARTICLES**

ltem.nr	Description	Concrete cover	Pcs/crt	Pcs/pallet	Unit
1002002	Markkloss 25/30	25-30 mm	300	5400	pcs
1002003	Markkloss 40/50	40-50 mm	250	4500	pcs
1002004	Markkloss 50/60	50-60 mm	200	3600	pcs
1002005	Markkloss 70/80	70-80 mm	125	2250	pcs
1002006	Markkloss 90/100	90-100 mm	100	1800	pcs

**OTHER INFORMATION** 



For this product there is CO<sub>2</sub>-emissions and EPD (environmental product declaration) available

# STORAGE

Store inside. Protect from exposure of direct sunlight during long periods of time.





We reserve the right for typographical errors and refer to the fact that the current version of the information is always available at www.hydratec.se or can be requested by contacting our office. The current version number can be found in the upper left corner