

TECHNICAL DATA SHEET - BTG.DISTANS ZICKZACK

DESCRIPTION

Concrete spacer in a zig-zag design with a continuous galvanized wire reinforcement to prevent breakage. The zig-zag shape ensures excellent stability on the surface.

APPLICATIONS

Suitable for use as a reinforcement spacer for heavy reinforcement and roll reinforcement in different types of construction projects.

When placing the spacer on slab formwork, it should be positioned with the pointed side facing the formwork.

Note: Despite this orientation, the spacer will still be visible even when the top is directed towards the formwork surface.



TECHNICAL INFORMATION

Material consumption: Ca 1-1,5 m/m²

Exposure classifications: XC4, XD2, XF4, XA2

Concrete cover: 25-80 mm

Lenght: ca 700-800 mm

c/c: ca 0,8m

Frost and compression tested

RANGE OF ARTICLES

Item.nr	Description	Lenght (mm)	Cover (mm)	Pcs/pallet	Weight/pallet (kg)	Unit
1004011	Btg.distans zickzack 25	800	25	1200	960	Pcs
1004012	Btg.distans zickzack 30	700	30	750	750	Pcs
1004013	Btg.distans zickzack 35	700	35	700	770	Pcs
1004014	Btg.distans zickzack 40	700	40	600	780	Pcs
1004015	Btg.distans zickzack 45	700	45	550	825	Pcs
1004016	Btg.distans zickzack 50	700	50	500	900	Pcs
1004017	Btg.distans zickzack 60	700	60	330	792	Pcs
1004018	Btg.distans zickzack 70	700	70	275	852,5	Pcs
1004019	Btg.distans zickzack 75	700	75	225	832,5	Pcs
1004121*	Btg.distans zickzack 80	800	80	275	1237,5	Pcs

*=Not in stock

OTHER INFORMATION



BVB ID
126692

STORAGE

Store the product on a pallet and protect it from damage, such as breakage, before it is cast in place. Apart from this, there are no specific storage guidelines. The product can be stored both indoors and outdoors year-round.