

TECHNICAL DATA SHEET - BETONGDISTANS RAK ANLÄGGNING

DESCRIPTION

Straight concrete spacer made of sulfate-resistant cement. Designed for spacing bottom reinforcement against the substrate.

APPLICATIONS

Suitable as a reinforcement spacer for heavy reinforcement and roll reinforcement. Ideal for use in construction projects, infrastructure, and projects with high requirements, such as those set by the Swedish Transport Administration (Trafikverket).



TECHNICAL INFORMATION

Material consumption: Ca 1-1,5 m/m²

Exposure classifications: XC4, XD3, XS3, XF3, XA3

Concrete cover: 30-100 mm

Lenght: ca 1000 mm

c/c: ca 0,8m

Frost and compression tested

RANGE OF ARTICLES

| Item.nr | Description | Lenght (mm) | Cover (mm) | Pcs/pallet | Weight/pallet (kg) | Unit |
|---------|----------------------------|-------------|------------|------------|--------------------|------|
| 1004020 | Betongdistans Rak 30 ANL. | 1000 | 30 | 700 | 1190 | Pcs |
| 1004021 | Betongdistans Rak 35 ANL. | 1000 | 35 | 570 | 1100 | Pcs |
| 1004022 | Betongdistans Rak 40 ANL. | 1000 | 40 | 470 | 1222 | Pcs |
| 1004024 | Betongdistans Rak 50 ANL. | 1000 | 50 | 330 | 1221 | Pcs |
| 1004025 | Betongdistans Rak 60 ANL. | 1000 | 60 | 250 | 1100 | Pcs |
| 1004026 | Betongdistans Rak 70 ANL. | 1000 | 70 | 170 | 850 | Pcs |
| 1004027 | Betongdistans Rak 80 ANL. | 1000 | 80 | 100 | 640 | Pcs |
| 1004028 | Betongdistans Rak 90 ANL. | 1000 | 90 | 100 | 740 | Pcs |
| 1004029 | Betongdistans Rak 100 ANL. | 1000 | 100 | 90 | 747 | Pcs |

OTHER INFORMATION



BVB ID
126692

STORAGE

Store the product on a pallet and protect it from damage, such as breakage, before it is cast in place. Apart from this, there are no specific storage guidelines. The product can be stored both indoors and outdoors year-round.