

## TECHNICAL DATA SHEET - BETONGKLOSS MED TRÅD

### DESCRIPTION

Concrete spacer in the shape as a "block" with wire is used to space reinforcement and ensure the correct concrete cover in reinforced concrete structures.

### APPLICATIONS

Can be used in all types of construction and infrastructure projects. The concrete block's exposure classes make it suitable for projects with high requirements, such as those set by the Swedish Transport Administration (Trafikverket).

### TECHNICAL INFORMATION

**Exposure classifications:** XC4, XD3, XS3, XF4, XA2

**Concrete cover:** 25-100 mm

Frost and compression tested



### RANGE OF ARTICLES

Item.nr	Description	Diameter (mm)	Cover (mm)	Pcs/bag	Pcs/pallet	Unit
1004030	Betongkloss 25 Tråd Anl.	35	25	285	11400	Pcs
1004031	Betongkloss 30 Tråd Anl.	54	30	110	4400	Pcs
1004032	Betongkloss 35 Tråd Anl.	54	35	95	3800	Pcs
1004033	Betongkloss 40 Tråd Anl.	54	40	80	3200	Pcs
1004034	Betongkloss 45 Tråd Anl.	54	45	70	2800	Pcs
1004035	Betongkloss 50 Tråd Anl.	54	50	60	2400	Pcs
1004036	Betongkloss 55 Tråd Anl.	54	55	55	2200	Pcs
1004037	Betongkloss 60 Tråd Anl.	54	60	50	2000	Pcs
1004038	Betongkloss 65 Tråd Anl.	54	65	45	1800	Pcs
1004039	Betongkloss 70 Tråd Anl.	54	70	40	1600	Pcs
1004044	Betongkloss 70/40 Tråd Anl.	40	70	75	3000	Pcs
1004043	Betongkloss 75 Tråd Anl.	54	75	38	1520	Pcs
1004040	Betongkloss 80 Tråd Anl.	54	80	35	1400	Pcs
1004045	Betongkloss 50/100 Tråd Anl.	100	50	30	1200	Pcs
1004046	Betongkloss 100/100 Tråd Anl.	100	100	15	480	Pcs

### OTHER INFORMATION



BVB ID  
126692



An Environmental Product Declaration (EPD) has been developed for this product.

### STORAGE

The product can be stored both indoors and outdoors year-round. If the product's packaging (bags) is exposed to direct sunlight for an extended period, it may become brittle and break.