TDS: VÄGGDISTANS KROK & NOPPOR

VER: 1.1

DATE: MAR 2025

SIDE: 1/1



TECHNICAL DATA SHEET - VÄGGDISTANS KROK & NOPPOR



DESCRIPTION

Väggdistans Krok & Noppor is a concrete reinforcement spacer for vertical applications, designed to ensure proper concrete cover in wall structures. Manufactured from high-quality concrete, it features an embedded hook for quick and easy attachment to wall reinforcement.

The nubbed design minimizes the contact surface with the formwork, enhancing concrete flow around the spacer and reducing the risk of air pockets.



APPLICATIONS

The wall spacer is used as a reinforcement spacer in wall formwork to ensure proper concrete cover in reinforced concrete structures. It maintains the correct distance between the reinforcement and the formwork, enhancing concrete durability and reducing the risk of corrosion.

TECHNICAL INFORMATION

Exposure classifications: XF4, XS3, XD3, XA3

Concrete cover: 20-60 mm (stocked dimensions listed below)

Tested for frostresistance and compressive strenght

RANGE OF ARTICLES

Item.nr	Description	Cover (mm)	Lenght (mm)	Pcs/pallet	Unit
1004070	Väggdistans Krok & Noppor 30	30	340	1800	Pcs
1004071	Väggdistans Krok & Noppor 35	35	340	1600	Pcs
1004072	Väggdistans Krok & Noppor 40	40	340	1300	Pcs
1004073	Väggdistans Krok & Noppor 45	45	340	1200	Pcs
1004074	Väggdistans Krok & Noppor 50	50	340	1100	Pcs
1004075	Väggdistans Krok & Noppor 60	60	340	800	Pcs

OTHER INFORMATION



STORAGE

The product can be stored both indoors and outdoors year-round.