



## IBS GROUP

### Our Production Facilities

- > IBS Technics GmbH Thierhaupten
- > IBS Technics Rotava (s.r.o.)
- > IBS Engineered Products Ltd, Doncaster, UK

### About Us

- > International Engineering Company
- > 150 employees
- > 11,000 m<sup>2</sup> manufacturing facilities
- > global leader for mobile flood water protection
- > more than 4000 successfully completed projects

### Our Performance

- > Global distribution
- > Development, design and construction
- > State of the art production
- > Modern machinery
- > International service structure

### Our Markets

- > Europe
- > Middle East
- > North America
- > Australia
- > Asia

**IBS GROUP**  
WWW.IBS-TECHNICS.DE

IBS Technics GmbH  
Gemeindewald 6 · 86672 Thierhaupten · Germany  
Tel.: + 49 (0) 8271 8176-0 · Fax: + 49 (0) 8271 8176-76  
Mail: info@ibs-technics.de · Web: www.ibs-technics.de

**IBS GROUP**  
WWW.IBSENGINEEREDPRODUCTS.CO.UK

Unit 7 · Brunel Park · Off Blyth Road · Harworth  
Doncaster · South Yorkshire · DN11 8NE  
Phone: +44 1302 6300-15 · Fax-Nr.: +44 1302 6300-14  
Mail: info@ibsengeeredproducts.co.uk · www.ibsengeeredproducts.co.uk

# IBS Flood Protection Glass Walls



- > Time-tested
- > Standardised solutions
- > International distribution structure
- > Economic serial Production
- > Complete portfolio of solutions

**IBS GROUP**  
WWW.IBS-TECHNICS.DE



## Glass Walls made by IBS

### Our experience – Your advantage

- > Capable
- > Tested
- > International
- > Qualified
- > Flexible
- > Resilient

### Quality Standards

- > DIN German Industrial Standard
- > EN 1090
- > Industrial Production
- > Certified Welding Specialists

### Sizes

- > Unlimited length, standard individual field sizes up to 2100 mm
- > Heights up to 1200 mm
- > Special designs and sizes on request

### Area of Application

- > Riverside areas
- > Seaside promenades
- > Public spaces
- > Private properties

### Advantages

- > Permanent flood protection
- > Maintenance friendly
- > Advanced, high performance system
- > Adaption to project specific requirements



## Components

- > Endposts
- > Center Posts
- > Anchor Plates
- > Frames
- > Laminated Safety Glass
- > Ground Seals

## References

- > Northwich (UK)  
Length: 330 m; max. Height: 1,4 m; Area: 358 m<sup>2</sup>
- > Leeds (UK)  
Length 103 m; max. Height: 1,3 m; Area: 86 m<sup>2</sup>
- > Bad Neustadt/Brend (D)  
Length: 340 m; max. Height 0,60 m; Area 204 m<sup>2</sup>
- > Paul Glass Wall, Hull (UK)  
Length: 520 m; max. Height: 1,1 m, Area: 550 m<sup>2</sup>
- > Upton upon Severn (UK)  
Length: 173 m; max. Height: 0,5 m; Area: 87 m<sup>2</sup>
- > Keswick (UK)  
Length: 120 m; max. Height 0,8 m; Area: 96 m<sup>2</sup>
- > Littlehampton (UK)  
Length: 82 m; max. Height: 0,8 m, Area: 66 m<sup>2</sup>
- > Penig (D)  
Length: 210 m; max. Height: 0,7 m; Area: 147 m<sup>2</sup>
- > Timmendorfer Strand (D)  
Length: 126; max. Height: 1,0 m; Area: 88 m<sup>2</sup>
- > Plauen (D)  
Length 200 m; max. Height: 1,0 m; Area: 200 m<sup>2</sup>
- > Decin (CZ)  
Length: 160 m; max. Height: 2,1 m; Area: 330 m<sup>2</sup>
- > Köln-Westhoven (D)  
Length: 310 m; max. Height: 0,4 m; Area: 125 m<sup>2</sup>

