

TECHNICAL DATA SHEET - VÄGG- & VALVKLOSS ALLROUND

DESCRIPTION

Vägg- & valvkloss allround is a PVC-free reinforcement spacer designed to ensure the correct distance between reinforcement and formwork when casting slabs and walls. It is nailable and has a small contact surface against the formwork, minimizing marks in the concrete. The spacer provides excellent concrete encapsulation and features two cover thicknesses per spacer.

For easy installation, it is equipped with clear height markings and can be pre-mounted at reinforcement intersections. Its concrete-gray color and slightly rounded feet make the spacer nearly invisible in the finished concrete surface.



TECHNICAL INFORMATION

Color: Grey

Material: PVC-free PE (Polyethylene)

Concrete cover: 15-55 mm (stock assortment in table below)

Rebar Ø: 4-20 mm

RANGE OF ARTICLES

ltem.nr	Description	Cover	Rebar Ø	Pcs/crt	Pcs/pallet	Unit
1003028	Vägg- & Valvkloss Allround 20-25	20-25mm	4-20 mm	900	16200	Pcs
1003029	Vägg- & Valvkloss Allround 30-35	30-35 mm	4-20 mm	700	12600	Pcs
1003030	Vägg- & Valvkloss Allround 40-45	40-45 mm	4-20 mm	600	10800	Pcs
1003031	Vägg- & Valvkloss Allround 50-55	50-55 mm	4-20 mm	500	9000	Pcs

OTHER INFORMATION



For this product there is CO₂-emissions and EPD (environmental product declaration) available

STORAGE

Store inside. Protect from exposure of direct sunlight during long periods of time.

We reserve the right for typographical errors and refer to the fact that the current version of the information is always available at www.hydratec.se or can be requested by contacting our office. The current version number can be found in the upper left corner