

## TECHNICAL DATA SHEET - BETONGDISTANS TREKANT

### DESCRIPTION

Concrete Spacer Triangular is a straight concrete spacer with a triangular profile. A continuous steel wire reinforcement enhances its strength and resistance to breakage.

### APPLICATIONS

Used as a reinforcement spacer in concrete structures to achieve the required concrete cover. Suitable for use as spacer on shutter end panels in walls to ensure the correct cover against the wall formwork.

### TECHNICAL INFORMATION

**Material consumption:** Ca 1-1,5 m/m<sup>2</sup>

**Exposure classifications:** XF4, XS3, XD3, XA2

**Concrete cover:** 30-100 mm

**Lenght:** ca 1000 mm

**c/c:** ca 0,8m

Frost and compression tested



### RANGE OF ARTICLES

Item.nr	Description	Cover (mm)	Lenght (mm)	Pcs/pallet	Unit
1004080	Betongdistans Trekant 30	30	1200	600	Pcs
1004081	Betongdistans Trekant 35	35	1200	500	Pcs
1004082	Betongdistans Trekant 40	40	1200	400	Pcs
1004083	Betongdistans Trekant 45	45	1200	300	Pcs
1004084	Betongdistans Trekant 50	50	1200	300	Pcs
1004085	Betongdistans Trekant 60	60	1200	200	Pcs

### OTHER INFORMATION



BVB ID  
126692



An Environmental Product Declaration (EPD) has been developed for this product.

### STORAGE

Store the product on a pallet and protect it from damage, such as breakage, before it is cast in place. Apart from this, there are no specific storage guidelines. The product can be stored both indoors and outdoors year-round.