

TECHNICAL DATASHEET - INJECTION HOSE HYDRA X1000

PROPERTIES

Injection hose HyDra X1000 is a newly developed, one-piece injection hose with a big core diameter. It is made from a specially formulated plastic, which features excellent usability characteristics. Following concreting, it functions as a channel for transporting the grouting material along the joint. Due to the extraordinary geometrical shape this hose is perfect for technically challenging injections with overlengths and various groutings. The hose is equipped with discharge ports, equally spaced over its entire circumference. This gives the injection hose optimum grouting characteristics. An optimization of the core diameter by means of an enlargement results in an improvement when injecting all kinds of groutings in particular cementitious based groutings.



APPLICATION

Injection hose HyDra X1000 can be applied for all kinds of technically challenging injections with various groutings once the concrete has cured.

TECHNICAL DATA

Profile:	round/hexagonal
Colour:	blue transparent
Material composition:	PVC-P special type for extrusion, conforms with ROHS, contains no substance of content according to SVHC-list, Phthalatfree production
Diameter	external: 18 mm internal: 10 mm
Metre markings at:	1m intervals
Lengths micro-ports:	approx. 5 mm spacing intervals: approx. 10 mm

PACKAGING & STORAGE

Dimension

coil: 60 m pallet: 28 rolls per 60 m = 1.680 m

Injection hose X1000 has to be stored in a dry place and protected against mechanical damage.

INSTALLATION

The concrete surface must be even, free of loose particles and sharp-edged displacements. Before installing Injection hose HyDra X1000 ice coverings, standing water and cement sludge have to be removed.

The regular hose length is 8-12 m.

Injection hose HyDra X1000 must lie flat on the surface of the first concrete section. The injection hose is secured with clamps or a fixing mesh. The distance between the clamps or fixing points should be 10-15 cm. This should be smaller if circumstances require.

Injection hose HyDra X1000 is in its ideal position when centrally aligned. The distance of the HyDra X1000 hose to the outer edge of the joint must be at least 10cm. At hose section joints, the two hoses are to overlap each other by 15cm and lie parallel one to another at a distance of 3-5 cm.

Injection:

Injection hose HyDra X1000 is injected after 28 days at the earliest.

Visible flaws along the construction joint are to be plugged with quick-dry cement before injecting.

TECHNICAL DATASHEET - INJECTION HOSE HYDRA X1000

Injection can be carried out in a number of ways:

⇒ Injection using an injector hose (reinforced PVC hose)

1. Check the continuity of the hose by flushing with water or air.
2. The hose is injected via the injection connector (PVC hose) until traces of the injected material are discharged from the open end. This open end is closed with an injection nipple as soon as the injected material starts to flow freely (without air pockets).
3. The flow and extent of the injection material in the concrete joint can be monitored during the injection process by means of the injection pump's pressure gauge.
4. The injection process continues until constant pressure has been reached. Constant pressure indicates that the concrete joint can take no more grouting material, thus signalling the end of the process.
5. Injection material in the injection hose is simply flushed out by means of a water pump (flushing pump from a 2-C pump unit). This operation requires hardly any pressure. The injection hose is then once again ready for additional injections. Flushing and reinjecting Injection hose X1000 is possible when injecting with Ultrafine cement respectively Polymer gel matrix.
6. Before injecting with ultra-fine cement (a mineral grout), WaterproofX® 1000 is flushed with water.
7. If Injection hose HyDra X1000 is injected with EP resin, PUR foam resin or PUR resin, both flushing and reinjecting the hose is not possible.

ACCESSORIES

Item nr. 1112221	Kopplingsdosa Injekterings slang X1000
Item nr. 1122212	Montageclips STÅL X1000 18 mm
Item nr. 1122213	Plugg X1000 ø10,8 mm
Item nr. 1122214	Slängklämma X1000
Item nr. 1122215	Injekteringsnippel X1000 Cement Två-delad
Item nr. 1122216	Skarvnippel PA X1000
Item nr. 1122217	Matarslang X1000 VIT 10x3,0 mm L=50 m
Item nr. 1122218	Matarslang X1000 BLÅ 10x3,0 mm L=50 m

We reserve the right for printing errors and refer to the fact that the current version of the data is always available at www.hydratec.se or can be requested by contacting our office. Current revision number is in the top left corner.