

## TECHNICAL DATA SHEET - DISTANSLINJAL ECO

### DESCRIPTION

Distanslinjal ECO is a linear concrete spacer made of cold-resistant, 100% recycled PVC-free plastic. It is used as a spacer for the bottom reinforcement on soft surfaces in reinforced concrete structures.

### USAGE

It is placed on soft surfaces with the wide base facing downward against the substrate.



### TECHNICAL INFORMATION

**Color:** Grey

**Material:** A blend of PVC-free PP and PE (Polyolefin blend)

**Concrete cover:** 25-60 mm (See stock assortment in the table below)

**Length:** 2.0 m

**Material consumption:** 1-1.5 m/m<sup>2</sup>

**c/c:** 0.8 m

### PROPERTIES

- Made from environmentally friendly and sustainable materials.
- Click-function
- Tested according to DBV Eurocode 2
- Can be used as a spacer of heavy reinforcement
- Cold-resistant
- EPD (Environmental product declaration)

### RANGE OF ARTICLES

Item.nr	Description	Height	Length	Bundle	Pallet	Unit
1001062	Distanslinjal ECO 30	30 mm	2,0 m	100	3600	m
1001063	Distanslinjal ECO 35	35 mm	2,0 m	60	2880	m
1001064	Distanslinjal ECO 40	40 mm	2,0 m	60	2100	m
1001066	Distanslinjal ECO 50	50 mm	2,0 m	56	1680	m

### OTHER INFORMATION



BVB ID  
167761



EPD (Environmental product declaration) is available for this product.

### STORAGE

Can be stored indoors or outdoors year-round. Storing in direct sunlight for extended periods can cause deformation or cracking.