

## TECHNICAL DATASHEET - HYDRA TOPSHIELD

### DESCRIPTION

HyDra Topshield is a highly concentrated, environmentally friendly accelerator for Rubber LM products. Topshield is applied on top of tge Rubber LM product, which accelerates the curing time of Rubber LM.

Topshield immediately removes a large part of the moisture percentage in Rubber LM causing an immediate "skin formation" on the product. This causes the products to dry faster and more resistant to, for example rainfall.

HyDra Topshield is an environmentally friendly product and can be used indoors and outdoors without special protection.

### APPLICATION

Spray Topshield lightly over the top layer of the Rubber LM product with an average distance of +- 20cm from the surface. Topshield should not be applied between two layers of Rubber LM, it should only be applied on the top layer. If Topshield is applied between different layers of Rubber LM it can damage the adhesion between the layers.

### RESTRICTIONS

Obey the safety precautions when applying by wearing gloves, eye protection and other suitable protective equipment. Please refer to the SDS sheet for more information.

### TECHNICAL DATA

PROPERTIES	TYPICAL RESULTS
Color	Transparant
Physical properties	Liquid
Specific gravity (liquid), g/cm <sup>3</sup>	CA. 1.0
Odor	None



### WARNING

Topshield should not be applied when the ambient temperature is lower than 0°C. During extreme rainfall is not recommended to use Topshield. For professional use only. Keep out of reach of children. Do not store product in direct sunlight, maximum 32°C (90°F) and minimum 5°C (41°F).