

TEKNISKT DATABLAD - HYDRA SEALANT

DESCRIPTION

HyDra Sealant is a pliable sealing compound used to seal cable- & pipeentries into underground structures such as basements, telecommunications vaults, storage tanks and sewer lines. HyDra Sealant is effective for repairing leaking structures such as building foundations, pools, penetrations and wastewater structures.

NOTE: Not intended for use in expansion joints och joints that move.

Properties:

- Bonds to wet surfaces
- No priming necessary
- Adheres to: Steel, concrete, PE, PP, PVC, rubber and wood
- Non-corrosive to pipe and cable coatings
- Non-curing, retains pliability for long term protection



TECHNICAL INFORMATION

Color	Green
Packaging	310 ml plastic cartridge
Specific gravity	ASTM D71*
Viscosity	ASTM D4**
pH	Neutral
Waterpressure	0,345 BAR = 3,45mvp
Application temp.	0-44°C
VOC	1,83-2,0%
Service temp.	-30°C-40°C
Shelf-life	36 months***
Storage	Store in a dry environment

Product has been tested and classified according to ASTM (American Society for testing materials)

*= ASTM D71 (Specific Gravity of Solid Pitch and Asphalt):

**= ASTM D4 (Bitumen Viscosity Test):

***= Since the product doesn't cure there is nothing to cause that the product would expire or make it to old for usage.

APPLICATION

Applicate HyDra Sealant with a caulking gun suitable for 310 ml cartridges.

NOTE: Applying HyDra Sealant with a caulking gun becomes more difficult in lower temperatures. Store HyDra Sealant close to a heat source when using HyDra Sealant in colder temperatures.

RANGE OF ARTICLES

Art.code	Description	pcs/crt	unit
1313002	HyDra Sealant 310ML	25	pcs

ADDITIONAL INFORMATION

You can find the safety data sheet for this product on our webpage www.hydratec.se

We reserve the right for printing errors and refer to the fact that the current version of the information is always available at www.hydratec.se or can be requested by contacting our office. Current version number is in the upper left corner.